



DN	L	D	D1	D2	b	D0	Z-Φd	-46°C	-101°C	-196°C	WT(kg)
DJ41Y-16C	DJ41Y-16P	DJ41Y-16R	DJ641Y-16C	DJ641Y-16P	DJ641Y-16R	DJ9B41Y-16C	DJ9B41Y-16P	DJ9B41Y-16R			
50	230	160	125	100	16	240	4-Φ18	460	480	520	-
65	290	180	145	120	18	280	4-Φ18	475	505	525	-
80	310	195	160	135	20	280	8-Φ18	520	550	590	-
100	350	215	180	155	20	320	8-Φ18	545	575	615	-
125	400	245	210	185	22	360	8-Φ18	590	620	660	-
150	480	280	240	210	24	400	8-Φ23	650	680	730	-
200	600	335	295	265	26	400	12-Φ23	850	880	930	-
250	730	405	355	320	30	450	12-Φ25	956	986	1036	-
300	850	460	410	375	30	500	12-Φ25	1095	1125	1175	-
DJ41Y-25	DJ41Y-25P	DJ41Y-25R	DJ641Y-25C	DJ641Y-25P	DJ641Y-25R	DJ9B41Y-25C	DJ9B41Y-25P	DJ9B41Y-25R			
50	230	160	125	100	20	240	4-Φ18	460	480	520	-
65	290	180	145	120	22	280	8-Φ18	475	505	525	-
80	310	195	160	135	22	280	8-Φ18	520	550	590	-
100	350	230	190	160	24	320	8-Φ23	545	575	615	-
125	400	270	220	188	28	360	8-Φ25	590	620	660	-
150	480	300	250	218	30	400	8-Φ25	650	680	730	-
200	600	360	310	278	34	400	12-Φ25	850	880	930	-
250	730	425	370	332	36	450	12-Φ30	956	986	1036	-
300	850	485	430	390	40	500	12-Φ30	1095	1125	1175	-
DJ41Y-40	DJ41Y-40P	DJ41Y-40R	DJ641Y-40C	DJ641Y-40P	DJ641Y-40R	DJ9B41Y-40C	DJ9B41Y-40P	DJ9B41Y-40R			
50	230	160	125	100	88	240	4-Φ18	483	504	546	-
65	290	180	145	120	110	280	8-Φ18	499	530	551	-
80	310	195	160	135	21	280	8-Φ18	546	578	620	-
100	350	230	190	160	150	320	8-Φ23	572	604	646	-
125	400	270	220	188	176	360	8-Φ25	620	651	693	-
150	480	300	250	218	204	400	8-Φ25	683	741	767	-
200	600	360	320	282	260	400	12-Φ30	893	924	977	-
250	730	425	385	345	313	450	12-Φ33	1004	1035	1088	-
300	850	485	450	408	364	500	12-Φ30	1150	1181	1234	-